
PHE 15 16.7 BEL STK (767 413)

- Easy transport due to detachable insulating stick
- Pluggable end fitting with eye allows to easily and safely climb the mast





Dimension drawing

For traction power lines
Hook-shaped electode and end fitting with plug-in coupling and non-slip eye included

Type	**PHE 15 16.7 BEL STK**
Part No.	**767 413**
Nominal voltage (U_N)	15 kV
Type of voltage	a.c.
Frequency	16.7 Hz
Total length (l_G)	1645 mm
Insertion depth (I_O)	765 mm
Insulating clearance (l_I)	525 mm
Length (test prod)	992 mm
Length of the operating stick (with hand guard)	638 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	–25 °C ... +55 °C, climatic category N
Design	Complete
For use at	
For	Outdoor installations
Application	Overhead contact lines of electric railways
Type	Single-pole
Indication	Visual
Self-testing element	Yes
Material (test prod)	**Glass-fibre reinforced epoxy resin tube**
Material (test electrode)	**Copper alloy/gal Sn**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**
DB drawing No.	3 Ebgw 02.55
DB Material No.	964 851

Masterdata	
Net weight	1.77 kg/pc(s)
GTIN	4013364128750
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component