
Datasheet: HSA 205 High-Voltage Indicator

HSA205 U 1 420 STK (767 552)





Dimension drawing

Type	HSA205 U 1 420 STK
Part No.	**767 552**
Nominal voltage range (U_N)	1 ... 30 / 30 ... 220 / 110 ... 420 kV
Frequency	50 Hz
Total length (l_c)	950 mm
Insulating clearance (l_i)	540 mm
Temperature range	–25 °C ... +55 °C, climatic category N
For use at	
Indication	Visual and acoustic
Self-testing element	Yes
Insulating stick material	**Glass-fibre reinforced polyester tube**

Masterdata	
Net weight	2 kg/pc(s)
GTIN	4013364115736
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component