Datasheet: ASP Non-Contact Voltage Detector Kit

ASPS 110 420 L (767 571)

- Insulating stick with plug-in coupling as end fitting for extending the handle
- In a suitable storage bag



Parts list:			
Pos.	Part No.	Pos.	Part No.
1	767 576	6	767 564
2	767 577	7	766 369
3	767 591	8	767 574
4	767 592	9	767 996
5	767 593		
For more detailed information on these products, see Accessories chapter.			

Kit includes:		
Type	Part No.	Pos. No.
ASP 110 420 L	767 581	1+3+7
KLT 104 9	767 574	8

Dimension drawing

Type	**ASPS 110 420 L**
Part No.	**767 571**
Nominal voltage (U_N)	110 ... 420 kV
Type of voltage	a.c.
Frequency	50 Hz
Total length (l_G)	960 mm
Category	L
Temperature range	–25 °C ... +55 °C
For use at	
For	Overhead lines and outdoor switching stations
Application	Overhead lines
Type	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (indicator)	**Plastic, fully insulated (black)**
Material (electric field sensor)	**Plastic (black)**
Insulating stick material	**Glass-fibre reinforced polyester tube**

Masterdata	
Net weight	1.99 kg/pc(s)
GTIN	4013364124967
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.