PHEG1 FD P 3 (767 610)





Dimension drawing

One stick (three elements)• For direct voltage systems with earthed negative pole
- Positive pole: indicator with test prod
- Negative pole: earth clamp
- Type: without magnet

Type	**PHEG1 FD P 3**
Part No.	**767 610**
Response voltage (U_T)	1.1 kV
Nominal voltage (U_N)	3.0 kV
Type of voltage	d.c.
Length (indicator with test prod) (l_S)	1245 mm
Length (insulating stick) (l_1)	1500 mm
Length (extension handle) (l_2)	1470 mm
Length (earthing cable)	6000 mm
Total length (l_G)	4125 mm
Earth clamp	Without magnet
Standard	Based on EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	–25 °C ... +55 °C, climatic category N
For use at	
For	Indoor and outdoor installations
Application	Overhead contact lines
Type	Two-pole
Indication	Visual
Self-testing element	Yes
Material (test electrode)	**Copper alloy/gal Sn**
Material (test prod)	**Glass-fibre reinforced polyester tube**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**
Material (connecting cable)	**Highly flexible copper cable**

Masterdata	
Net weight	4.4 kg/pc(s)
GTIN	4013364135208
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component