
PHEG2 P SN7552 (767 647)





Dimension drawing

Type	PHEG2 P SN7552
Part No.	**767 647**
Response voltage (U_T)	90 V
Nominal voltage (U_N)	1 ... 4.2 kV
Type of voltage	d.c.
Length (indicator with test prod) (l_S)	300 mm
Length (insulating stick) (l_1)	365 mm
Length (connecting cable)	1200 mm
Total length (l_G)	600 mm
Standard	Based on EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	–25 °C ... +55 °C, climatic category N
For use at	
For	Indoor and outdoor installations
Application	Switchgear installations
Type	Two-pole
Indication	Visual
Self-testing element	Yes
Material (test electrode)	**Copper alloy/gal Sn**
Material (test prod)	**Glass-fibre reinforced polyester tube**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**
Material (connecting cable)	**Highly flexible copper cable**

Masterdata	
Net weight	2.1 kg/pc(s)
GTIN	4013364156081
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.