
PHE3 30 S ZK (767 930)

- Easy transport due to detachable insulating stick (ZK) and test prod
- Insulating stick with plug-in coupling for extending the handle





Dimension drawing

Type	PHE3 30 S ZK
Part No.	**767 930**
Nominal voltage (U_N)	30 kV
Type of voltage	a.c.
Category	S 62
Total length (l_6)	1485 mm
Insertion depth (I_O)	620 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	-25 °C ... +55 °C, climatic category N
Design	Complete
For use at	
For	Indoor and outdoor installations
Application	Switchgear installations and overhead lines
Type	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (test electrode)	**Copper alloy/gal Sn**
Material (test prod)	**Glass-fibre reinforced epoxy resin tube**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**

Masterdata	
Net weight	1.17 kg/pc(s)
GTIN	4013364134775
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.