
Datasheet: PHE III Voltage Detector Kit

PHE3 60 110 S (767 990)





Dimension drawing

Type	PHE3 60 110 S
Part No.	**767 990**
Nominal voltage (U_N)	60 ... 110 kV
Type of voltage	a.c.
Frequency	50 Hz
Category	S
Total length (I_G)	2980 mm
Insertion depth (I_O)	880 mm
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Temperature range	–25 °C ... +55 °C, climatic category N
Design	Complete
For use at	
For	Indoor and outdoor installations
Application	Switchgear installations and overhead lines
Type	Single-pole
Indication	Acoustic and visual
Self-testing element	Yes
Material (test electrode)	**Copper alloy/gal Sn**
Material (test prod)	**Glass-fibre reinforced epoxy resin tube**
Material (indicator)	**Plastic, fully insulated**
Insulating stick material	**Glass-fibre reinforced polyester tube**

Masterdata	
Net weight	2.7 kg/pc(s)
GTIN	4013364135956
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90303370

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component