
# ESTC SQL STK 3000 (769 300)

- For outdoor use
- Robust aluminium cone coupling
- Telescopic stick, length continuously adjustable by star knob
- For phase screw clamps and clamps with long T pin shaft
- With plug-in coupling






Dimension drawing

| Type | ESTC SQL STK 3000 |
|---|---|
| **Part No.** | **769 300** |
| Total length ($l_{G\,max}$ / $I_{G\,min}$) | 3015 / 1760 mm |
| Length (handle) ($I_H$) | 900 mm |
| Max. load on the operating head ($l_{G\,max}$ / $I_{G\,min}$) | 10 / 20 kg |
| Temperature range | –25 °C ... +55 °C |
| Material (insulating tube) | **Glass-fibre reinforced polyester tube** |
| Material (threaded coupling, star knob) | **Aluminium alloy** |
| Diameter | 43 mm |
| Supporting head for | T pin shaft |
| Anti-rotation plug-in coupling including end fitting | Yes |
| Type of device | Earthing stick |

| **Masterdata** | |
|---|---|
| Net weight | 2.8 kg/pc(s) |
| GTIN | 4013364080867 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 82055980 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.