
EST KS SQL 1500 (769 503)

- Aluminium bayonet coupling with adjusting ring to fix the attached overhead line clamp
- Positive connection due to aluminium threaded coupling



Permissible loads for the earthing sticks:		
Length l_G	Pos. No.	Max. load on the operating head
6000 mm	**1**+**2**+**2**+**3**	3.5 kg
4500 mm	**1**+**2**+**3**	10 kg
3000 mm	**1**+**3**	10 kg
1500 mm	**1**	20 kg



Dimension drawing

Type	**EST KS SQL 1500**
Part No.	**769 503**
Total length (l_G)	1600 mm
Max. load on the operating head	20 kg
Temperature range	–25 °C ... +55 °C
Material (insulating tube)	**Glass-fibre reinforced polyester tube**
Material (threaded coupling, star knob)	**Aluminium alloy**
Material (threaded coupling)	**Aluminium alloy**
Diameter	43 mm
Supporting head for	T pin shaft
Type of device	Earthing stick - top section

Masterdata	
Net weight	1.65 kg/pc(s)
GTIN	4013364003996
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component