
ESTC PSK 5000 SN7249 (769 511)

- Earthing and short-circuiting devices can be configured online via the EaS configurator
- For connecting the phase cables of single-pole and three-pole earthing and short-circuiting devices to the overhead line
- With long threaded T pin shaft
- Wide clamping range





Dimension drawing

Type	ESTC PSK 5000 SN7249
Part No.	**769 511**
Clamping range Ø	10 ... 85 mm
Anti-rotation protection	PK2
For cable cross section Cu	16 ... 150 mm²
Max. short-circuit current I_k 0.5 s	29.6 kA
Max. short-circuit current I_k 1 s	29.6 kA
Standard	EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087
Temperature range	–25 °C ... +55 °C
Pressure plate material	**Aluminium alloy**
Material (clamp body)	**Aluminium alloy**
Material (shaft)	**StSt**
Material (coupling aid)	**St/gal Zn**
Material (insulating tube)	Glass-fibre reinforced polyester tube
Material (threaded coupling, star knob)	**Aluminium alloy**
Total length ($l_{G\,max}$ / $I_{G\,min}$)	5200 / 2875 mm
Length (handle)	1900 mm
Diameter (stick)	43 mm

Masterdata	
Net weight	4.41 kg/pc(s)
GTIN	4013364135055
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

The clamps must be designed for the same maximum short-circuit current as the earthing and short-circuiting cables!

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component