
UK 30 SK (773 130)

- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator





*) Clamping range and maximum cable cross-section of universal clamps used for:

Fixed ball point Ø	Phase T pin collar width	Rd / Fl clamping range	Cable cross-section
20/25/30 mm	15/18 mm	20/30 mm	16 mm²
20/25/30 mm	15/18 mm	20/30 mm	25 mm²
20/25/30 mm	15/18 mm	20/30 mm	35 mm²
20/25/30 mm	15/18 mm	20/30 mm	50 mm²
20/25/30 mm	15/18 mm	20/30 mm	70 mm²
20/25/30 mm	15/18 mm	–	95 mm²
–/25/30 mm	–	–	120 mm²
–	–	–	150 mm²

Dimension drawing

Type	UK 30 SK
Part No.	**773 130**
For fixed ball point Ø	25 / 30 mm
For T pins with a collar width of	18 mm
Terminal lug material	**Cualloy / gal Sn**
Material (shaft)	**Copper alloy/gal Sn**
Rd / Fl clamping range	30 mm
Pressure plate material	**St/gal Zn**
Anti-rotation protection	PK1
For cable cross section Cu	16 ... 120*) mm²
Max. short-circuit current I_k 0.5 s	33.5 kA
Max. short-circuit current I_k 1 s	23.7 kA
Standard	EN/IEC 61230 (DIN VDE 0683- 100)
Temperature range	–25 °C ... +55 °C
Material (clamp body)	**Copper alloy/gal Sn**

Masterdata	
Net weight	801 g/pc(s)
GTIN	4013364057722
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) See table for „Clamping range and maximum cable cross-section of universal clamps used for“

The clamps must have the same maximum short-circuit current as the earthing and short-circuiting cables!