
UK 25 SQL (773 236)

- Earthing and short-circuiting devices can be configured online by means of the earthing and short-circuiting configurator





Dimension drawing

*) Clamping range and maximum cable cross-section of universal clamps used for:

Fixed ball point Ø	Phase T pin collar width	Rd / Fl clamping range	Cable cross-section
20/25/30 mm	15/18 mm	20/30 mm	16 mm²
20/25/30 mm	15/18 mm	20/30 mm	25 mm²
20/25/30 mm	15/18 mm	20/30 mm	35 mm²
20/25/30 mm	15/18 mm	20/30 mm	50 mm²
20/25/30 mm	15/18 mm	20/30 mm	70 mm²
20/25/30 mm	15/18 mm	–	95 mm²
–/25/30 mm	–	–	120 mm²
–	–	–	150 mm²

Type	UK 25 SQL
Part No.	**773 236**
For fixed ball point Ø	20 / 25 mm
For T pins with a collar width of	15 mm
Rd / Fl clamping range	20 mm
Anti-rotation protection	PK1
For cable cross section Cu	16 … 120*) mm²
Max. short-circuit current I_k 0.5 s	33.5 kA
Max. short-circuit current I_k 1 s	23.7 kA
Standard	EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087
Temperature range	–25 °C … +55 °C
Pressure plate material	**St/gal Zn**
Material (clamp body)	**Copper alloy/gal Sn**
Material (shaft)	**Copper alloy/gal Sn**
Material (coupling aid)	**St/gal Zn**

Masterdata	
Net weight	713.5 g/pc(s)
GTIN	4013364114579
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) See table for „Clamping range and maximum cable cross-section of universal clamps used for“

The clamps must be designed for the same maximum short-circuit current as the earthing and short-circuiting cables!