
UK K25 FL30 SQL (773 251)

- Universal clamp, T pin shaft
- T pin according to DIN 48087
- For flat and round conductors up to 30 mm and fixed ball points, ball Ø25 mm





*) Klemmbereich und Seilquerschnitt für Uniklemmen an:

Kugelfestpunkt Ø	T-Anschluss Halsweite	Rd / Fl Klemmbereich	Seilquerschnitt
20/25/30 mm	15/18 mm	20/30 mm	16 mm²
20/25/30 mm	15/18 mm	20/30 mm	25 mm²
20/25/30 mm	15/18 mm	20/30 mm	35 mm²
20/25/30 mm	15/18 mm	20/30 mm	50 mm²
20/25/30 mm	15/18 mm	20/30 mm	70 mm²
20/25/30 mm	15/18 mm	–	95 mm²
–/25/30 mm	–	–	120 mm²
–	–	–	150 mm²

Dimension drawing

Type	UK K25 FL30 SQL
Part No.	**773 251**
For fixed ball point Ø	25 / 30 mm
Anti-rotation protection	PK2 (Ø10.5 mm)
For cable cross section Cu	50 mm²
Max. short-circuit current I_k 0.06 s	34.0 kA
DB drawing No.	4 Ebgw 01.59
DB Material No.	157 538
Pressure plate material	**St/gal Zn**
Material (clamp body)	**Copper alloy**
Material (shaft)	**Stainless steel**

Masterdata	
Net weight	901 g/pc(s)
GTIN	4013364005990
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.