
UK K25 FL30 HG (774 251)

- Universal clamp with plastic handle
- For flat and round conductors up to 30 mm and fixed ball points, ball Ø25 mm





*) Klemmbereich und Seilquerschnitt für Uniklemmen an:

Kugeleck-punkt Ø	T-Anschluss Halsweite	Rd / FF Klemmbereich	Seilquer-schnitt
20/25/30 mm	15/18 mm	20/30 mm	16 mm²
20/25/30 mm	15/18 mm	20/30 mm	25 mm²
20/25/30 mm	15/18 mm	20/30 mm	35 mm²
20/25/30 mm	15/18 mm	20/30 mm	50 mm²
20/25/30 mm	15/18 mm	20/30 mm	70 mm²
20/25/30 mm	15/18 mm	–	95 mm²
–/25/30 mm	–	–	120 mm²
–	–	–	150 mm²

Dimension drawing

Type	**UK K25 FL30 HG**
Part No.	**774 251**
For fixed ball point Ø	25 / 30 mm
Anti-rotation protection	PK2 (Ø10.5 mm)
For cable cross section Cu	50 mm²
Max. short-circuit current I_k 0.06 s	34.0 kA
DB drawing No.	4 Ebgw 01.64
DB Material No.	157 537
Pressure plate material	**St/gal Zn**
Material (clamp body)	**Copper alloy**
Material (shaft)	**Stainless steel**

Masterdata	
Net weight	955 g/pc(s)
GTIN	4013364006003
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component