
PHE4 Voltage Detector (British Influenced Voltage Level)

PHE4 33 S (783045)





Dimension drawing

Type	PHE4 33 S
Part No.	**783045**
Nominal voltage (U_N)	33 kV
Temperature range	–25 °C ... +70 °C, climatic category N and W
Type of voltage	a.c.
Frequency	50 Hz
Category	S
For	Indoor and outdoor installations
Total length (l_G)	1720 mm
Insertion depth (l_O)	920 mm
Length (handle) (l_H)	265 mm
Material (test prod)	**Glass-fibre reinforced epoxy resin tube**
Material (indicator)	**Plastic, fully insulated**
Standard	EN/IEC 61243-1 (DIN VDE 0682-411)
Insulating stick material	**Glass-fibre reinforced polyester tube**
Design	Complete
For use in wet weather conditions	Yes
Application	Switchgear installations and overhead lines
Type	Single-pole
Indication	Acoustic and visual
Sound level	> 67 dB(A) (visual indication and intermittent sound signal)
Self-testing element *)	**Yes**
Battery	Lithium AA 1.5 Volt
Material (test electrode)	**Copper alloy/gal Sn**
Diameter (insulating stick)	30 mm

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	90303370
GTIN	4013364310094
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) all circuits including test prod