
PSK 10 85 SQL (784 085)

- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator
- For connecting the phase cables of single-pole and three-pole earthing and short-circuiting devices to the overhead line
- With long threaded T pin shaft
- Wide clamping range





Dimension drawing

Type	PSK 10 85 SQL
Part No.	**784 085**
Clamping range Ø	10 ... 85 mm
Anti-rotation protection	PK2
For cable cross section Cu	16 ... 150 mm²
Max. short-circuit current I_k 0.5 s	29.6 kA
Max. short-circuit current I_k 1 s	29.6 kA
Standard	EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087
Temperature range	–25 °C ... +55 °C
Pressure plate material	**Aluminium alloy**
Material (clamp body)	**Aluminium alloy**
Material (shaft)	**StSt**
Material (coupling aid)	**St/gal Zn**

Masterdata	
Net weight	872 g/pc(s)
GTIN	4013364018686
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85359000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

The clamps must be designed for the same maximum short-circuit current as the earthing and short-circuiting cables!