
APT OD YE 48 (785 361)





Dimension drawing

Type	APT OD YE 48
Part No.	**785 361**
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Standard	IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611
Arc energy (W_{arc} oder W_{LBP})	320 kJ
Material	**Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%)**
Arc rating – ATPV (open arc)	16 cal / cm² *)
Arc rating – ELIM (open arc)	13 cal / cm²
PPE category (NFPA 70E)	PPE 2
Weight per unit area	300 g/m²
Material (sewing thread)	**Kevlar (100%)**
Primary colour	fluorescent yellow
Secondary colour	grey
Zipper	red
Size (international)	48 (S)

Masterdata	
Net weight	777 g/pc(s)
GTIN	4013364452176
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	62034911

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) Outer fabric after preparation