LED HL ESH (785 723)



- Fits the slot in the ESH U S safety helmet for electricians, in connection with face shield APS CL1 MEHA and APS CL2 MAHA
- With two separate reflectors for long-distance beam and wide-area light, with 4 switch levels
- Two charging options: micro USB or charging cradle. Charger with charging cradle included in delivery

Type	LED HL ESH
Part No.	**785 723**
Degree of protection	IP 67
Power source	lithium battery
Operating temperature range	-20 °C ... +50 °C
Max. luminous flux	115 lumens

Masterdata	
Net weight	148 g/pc(s)
GTIN	4013364360266
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85318070

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component