APHO AS (785 750)

- High wearing comfort
- High degree of protection and low wear due to energy-absorbing nanoparticles
- Excellent visibility due to anti-mist coating and high light transmittance



Type	**APHO AS**
Part No.	**785 750**
Material	**plastic, neoprene, leather**
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (W_{arc} oder W_{LBP})	320 kJ
Arc Rating – ATPV (Open Arc Test)	37.2 cal / cm^2
PPE category (NFPA 70E)	PPE 3
Visible light transmittance (VLT)	29.1 ... 43.2 %
Standard	GS-ET-29; IEC 61482-1-2; IEC 61482-1-1, EN 166, EN 170

Masterdata	
Net weight	0.8 kg/pc(s)
GTIN	4013364529694
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	65061080

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component