APB APC2 29C (785 790)

- High wearing comfort
- High degree of protection and low wear due to energy-absorbing nanoparticles
- Excellent visibility due to anti-mist coating and high light transmittance



Type	**APB APC2 29C**
Part No.	**785 790**
Material	**Modacrylic (55%), cotton (45%)**
Standard	EN ISO 13688, EN ISO 11612, EN 61482-1-2
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2 *)
Arc energy (W_{arc} oder W_{LBP})	320 kJ
Arc Rating – ATPV (Open Arc Test)	29 cal / cm^2
PPE category (NFPA 70E)	PPE 3
Colour	navy blue
Size (international)	One size

Masterdata	
Net weight	166.67 g/pc(s)
GTIN	4013364489776
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	62149000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) Outer fabric after preparation

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component