
APG GREY 9 L (785 862)

- Excellent fit due to special glove cut
- Good touch sensitivity due to soft leather inner surface of the gloves
- Comfortable to wear due to the use of breathable materials





Dimension drawing

Type	APG GREY 9 L
Part No.	**785 862**
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc energy (APC 2) (W_{arc} oder W_{LBP})	320 kJ
Arc energy (APC 1 150) (W_{arc} oder W_{LBP})	168 kJ
Arc Rating – ATPV (Open Arc Test)	35 cal / cm²
PPE category (NFPA 70E)	PPE 3
Total length	430 mm
Gauntlet length	230 mm
Size (international)	9 (L)
Material (glove palm)	**Siliconised calf grain leather**
Material (glove back)	**100% Kevlar interlock knit**
Material (sewing thread)	**Kevlar**
Standard	GS-ET 42-2, ASTM F2675, EN 388, EN 407

Masterdata	
Net weight	390 g/paa
GTIN	4013364486393
PU	1 PAA
Customs tariff number (Comb. Nomenclature EU)	42032910

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component