TFRS MS (785 950)

- Transparent intake tubes for enhanced safety
- Universal gear coupling for replacing and adjusting the angle of operating heads
- Delivered in a suitable transport case



Type	TFRS MS
Part No.	**785 950**
Nominal voltage (U_N)	Up to 36 kV
Frequency range	15 ... 60 Hz
Dimensions (bag)	1400 x 280 mm
Dimensions (case)	900 x 415 x 430 mm
Standard	Based on DIN VDE 0681-1 and DIN VDE 0682-621
Standard (universal gear coupling)	EN/IEC 60832 (DIN VDE 0682-211)
For use at	✷

Masterdata	
Net weight	27.3 kg/pc(s)
GTIN	4013364106383
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	82055980

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component