# APPS BC L (787 004)



| Type | APPS BC L |
|---|---|
| **Part No.** | **787 004** |
| Arc fault protection class (box test 4 kA / 0.5 s – single-pole) | APC 1 |
| Arc power ($W_{arc}$ or $W_{LBP}$) | 168 kJ |
| Arc Rating – ATPV (Open Arc Test) | 5.4 cal / $cm^2$ |
| Standards | EN 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471 |
| Material | Cotton (50%), modacrylic (39%), viscose (10%), static inhibitors (1%) |
| Weight per unit area | 160 $g/m^2$ |
| Size (international) | L |
| Colour | fluorescent yellow/blue |
| High-visibility clothing class | 1 |

| Masterdata | |
|---|---|
| Net weight | 486.66 g/pc(s) |
| GTIN | 4013364482425 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 61051000 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component