APUP XL (787 025)



Type	APUP XL
Part No.	**787 025**
Arc fault protection class (box test 4 kA / 0.5 s – single-pole)	APC 1
Arc power (W_{arc} or W_{LBP})	168 kJ
Arc Rating – ATPV (Open Arc Test)	4.1 cal / cm²
in combination with DEHNcare ArcFit Indoor	31 cal / cm²
in combination with DEHNcare ArcFit Outdoor	37 cal / cm²
Arc Rating – ELIM (in combination with DEHNcare ArcFit Indoor)	28 cal / cm²
Arc Rating – ELIM (in combination with DEHNcare ArcFit Outdoor)	34 cal / cm²
Standards	IEC 61482-2, EN ISO 11612, EN 1149-5
Material	Cotton (50%), modacrylic (39%), viscose (10%), static inhibitors (1%)
Weight per unit area	160 g/m²
Size (international)	XL
Colour	blue

Masterdata	
Net weight	260 g/pc(s)
GTIN	4013364482456
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	61034200

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component