KL-C-ARC-8-41-S (787 100)



Type	KL-C-ARC-8-41-S
Part No.	**787 100**
Category	RC
Standard	EN 60903, IEC 61482-1-2, ASTM F2675/F2675M-22e1
Max. operating voltage	7.5 kV AC (11.25 kV DC)
Test voltage	10 kV
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
ATPV	7.2 cal / cm²
Total length	410 mm
Wall thickness	1.5 mm
Size	8
Packaging colour	white

Masterdata	
Net weight	430 g/paa
GTIN	4013364483118
PU	1 PAA
Customs tariff number (Comb. Nomenclature EU)	40151900

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component