Datasheet: Insulating gloves up to 36 kV

KL-D-ARC-9-41-S (787 105)



Type	KL-D-ARC-9-41-S
Part No.	**787 105**
Category	RC
Standard	EN 60903, IEC 61482-1-2, ASTM F2675/F2675M-22e1
Max. operating voltage	17 kV AC (25.5 kV DC)
Test voltage	20 kV
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
ATPV	16 cal / cm²
Total length	410 mm
Wall thickness	2.3 mm
Size	9
Packaging colour	white / yellow

Masterdata	
Net weight	650 g/paa
GTIN	4013364483163
PU	1 PAA
Customs tariff number (Comb. Nomenclature EU)	40151900

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component