# KL-D-ARC-10-41-S (787 106)



| Type | KL-D-ARC-10-41-S |
|---|---|
| **Part No.** | **787 106** |
| Category | RC |
| Standard | EN 60903, IEC 61482-1-2, ASTM F2675/F2675M-22e1 |
| Max. operating voltage | 17 kV AC (25.5 kV DC) |
| Test voltage | 20 kV |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2 |
| ATPV | 16 cal / cm² |
| Total length | 410 mm |
| Wall thickness | 2.3 mm |
| Size | 10 |
| Packaging colour | white / yellow |

| Masterdata | |
|---|---|
| Net weight | 650 g/paa |
| GTIN | 4013364483170 |
| PU | 1 PAA |
| Customs tariff number (Comb. Nomenclature EU) | 40151900 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component