# ES4FI G - 1 X 4 (787 474)

- For protection against accidental and direct contact with live parts



| Type | ES4FI G - 1 X 4 |
|---|---|
| **Part No.** | **787 474** |
| Class | 4 |
| Nominal voltage up to ($U_N$) | 36 kV AC (54 kV DC) |
| Material | **Natural rubber / SBR** |
| Temperature resistance | -40°C to +65°C |
| Length | 4 m |
| Width | 1000 mm |
| Thickness | 5.2 mm |
| Colour | Grey |
| Standard | EN/IEC 61111 |

| Masterdata | |
|---|---|
| Net weight | 33.28 kg/pc(s) |
| GTIN | 4013364513778 |
| PU | 1 pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 40082110 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component