# KC-AI-9-36-S (787 491)



| Type | KC-AI-9-36-S |
|---|---|
| **Part No.** | **787 491** |
| Category | RC |
| Class | 00 |
| Max. operating voltage | 500 V AC (750 V DC) |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2 |
| Arc rating in accordance with ASTM F2675 | 14 cal / $cm^2$ |
| Colour | black |
| Wall thickness | 1.8 mm |
| Total length | 360 mm |
| Size | 9 |
| Material | **Natural rubber** |
| Standard (gloves) | EN 60903, IEC 61482-1-2, ASTM F2675/F2675M-22e1 |

| Masterdata | |
|---|---|
| Net weight | 346.67 g/paa |
| GTIN | 4013364479968 |
| PU | 1 PAA |
| Customs tariff number (Comb. Nomenclature EU) | 40151900 |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component