KC-BI-9-36-S (787 495)



Type	KC-BI-9-36-S
Part No.	**787 495**
Category	RC
Class	0
Max. operating voltage	1,000 V AC (1,500 V DC)
Arc fault protection class (box test 7 kA / 0.5 s – single-pole)	APC 2
Arc rating in accordance with ASTM F2675	25 cal / cm^2
Colour	black
Wall thickness	2.3 mm
Total length	360 mm
Size	9
Material	**Natural rubber**
Standard (gloves)	EN 60903, IEC 61482-1-2, ASTM F2675/F2675M-22e1

Masterdata	
Net weight	433.33 g/paa
GTIN	4013364480001
PU	1 PAA
Customs tariff number (Comb. Nomenclature EU)	40151900

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component