RD 10 STTZN L2000 (800 908)



With zinc coating ≥ 50 µm on average (about 350 g/m²). Suitable for installation in reinforcements (e.g. concrete supports or concrete foundations).

Type	RD 10 STTZN L2000
Part No.	**800 908**
Diameter Ø conductor	10 mm
Cross section	78 mm²
Material	**St/tZn**
Standard	based on EN 62561-2
Zinc coating	≥ 50 µm average (about 350 g/m²)
Specific conductance	≥ 6.66 m / Ohm mm²
Specific resistance	≤ 0.25 Ohm mm² / m
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	5.5 kA
Length	2 m
Length tolerance	+/- 5%

Masterdata	
Net weight	1.28 kg/pc(s)
GTIN	4013364486836
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	72149939

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Conductor materials can only be supplied in the original coil weights.
Further conductor materials as specified in the standard series EN 62561-2 are available on request.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component