BA 30X3.5 STTZN R50M (810 335)



Steel strip according to EN 62561-2 with zinc coating ≥ 70 µm on average (about 500 g/m²), for lightning protection and earth-termination systems.

Type	**BA 30X3.5 STTZN R50M**
Part No.	**810 335**
Width	30 mm
Thickness	3.5 mm
Cross section	105 mm²
Material	**St/tZn**
Standard	EN 62561-2
Zinc coating	≥ 70 µm average (about 500 g/m²)
Specific conductance	≥ 6.66 m / Ohm mm²
Specific resistance	≤ 0.15 Ohm mm² / m
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	7.4 kA
Length tolerance	+/- 5%

Masterdata	
Net weight	1 kg/kg
GTIN	4013364032880
PU	1 KG
Customs tariff number (Comb. Nomenclature EU)	72123000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Strips in different dimensions and materials are available upon request.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component