BA 50X4 ST R30M (810 503)



Bare steel strip 200mm² for use in earthing installations for railway systems that are welded (Ril 997.0205A01) and as per DIN EN 62561-2 (VDE 0185-561-2), for use in lightning protection and earthing systems.

Type	BA 50X4 ST R30M
Part No.	**810 503**
Width	50 mm
Thickness	4 mm
Cross section	200 mm²
Material	**St/bare (S235 JR)**
Short-circuit current	> 25 kA
Test current	40 kA / 100 ms
Standard	DIN EN 62561-2 (VDE 0185-561-2)
Guideline	Ril 997.0205A01
Specific conductance	≥ 6.66 m / Ohm mm²
Specific resistance	≤ 0.15 Ohm mm² / m
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	14 kA
Length tolerance	+/- 5%

Masterdata	
Net weight	1 kg/kg
GTIN	4013364534421
PU	1 KG
Customs tariff number (Comb. Nomenclature EU)	72111900

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Strips in different dimensions and materials are available upon request.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEW: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component