# HVI light Conductor

## HVI LI 45 20 L .. GR M (819129)




| Type | HVI LI 45 20 L .. GR M |
|---|---|
| **Part No.** | **819129** |
| Material of conductor | Cu |
| Material of insulation | PE |
| Sheath material | PE |
| Colour of conductor | dark grey |
| RAL colour | similar to 7000 |
| Cross-section of core | 19 mm² |
| Lightning current carrying capability (class / $I_{imp}$) | H1 / 150 kA |
| Equivalent separation distance s (air) | ≤ 45 cm |
| Diameter Ø conductor | 20 mm |
| Characteristics of sheath | UV stabilised and weather-resistant |
| Minimum order length (l1) | 6 m |
| Standard | DIN EN IEC 62561-8 (VDE 0185-561-8) |

| Masterdata | |
|---|---|
| Net weight | 3.16 kg/pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85446010 |
| GTIN | 4013364223158 |
| PU | 1 pc(s) |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component