
HVI Conductor / HVI long Conductor

HVI RAV 75 23 L6M GR M (819227)





Dimension drawing

Please specify conductor length when ordering (0.5 m steps).

Type	HVI RAV 75 23 L6M GR M
Part No.	**819227**
Material of conductor	Cu
Material of insulation	PE
Sheath material	PE
Colour of conductor	grey
RAL colour	similar to 7035
Cross section of core (stranded)	19 mm²
Lightning current carrying capability (class / I_{imp})	H1 / 150 kA
Equivalent separation distance s (air)	≤ 75 cm
Diameter Ø conductor	23 mm
Characteristics of sheath	UV-stabilised and weather-resistant
Connection diameter	10 mm
Material of connection elements	StSt
Minimum order length	6 m
Touch protection	Yes (as per DS2094)
Standard	DIN EN IEC 62561-8 (VDE 0185-561-8)

Masterdata	
Net weight	3.9 kg/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85446010
GTIN	4013364157712
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component