
# CUI Conductor

## CUI L 20 GR 3.5M (830208)





Dimension drawing

| Type | CUI L 20 GR 3.5M |
|---|---|
| **Part No.** | **830208** |
| Material of conductor | Cu |
| Material of insulation | XLPE |
| Surge withstand capability (1.2/50 µs) | 100 kV |
| Diameter Ø conductor | 20 mm |
| Standard | EN 62561-2 |
| Colour of conductor | light grey |
| Cross section of core | 50 mm² |
| Total length | 3500 mm |

| Masterdata | |
|---|---|
| Net weight | 2.6 kg/pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 85389099 |
| GTIN | 4013364106116 |
| PU | 1 pc(s) |

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN (U.K.) LTD. • Unit 4 Velocity Point • Castleton Road • Armley • Leeds • LS12 2EE • United Kingdom • Tel. +44 113 541 8900 • info@dehn.co.uk • www.dehn.co.uk

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component