BA 40X5 V4A R30M (860 405)



Stainless steel strip according to EN 62561-2, for lightning protection systems and ring equipotential bonding.

Stainless steel strips for use in soil have to be made of StSt (V4A) with a molybdenum content > 2 % e.g. 1.4571, 1.4404 in accordance with EN 62561-2, IEC/EN 62305-3 and DIN VDE 0151.

Type	**BA 40X5 V4A R30M**
Part No.	**860 405**
Width	40 mm
Thickness	5 mm
Cross section	200 mm²
Material	StSt (V4A)
Material No.	1.4571 / 1.4404
Standard	EN 62561-2
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300 °C)	7.4 kA
Length tolerance	+/- 5%

Masterdata	
Net weight	1 kg/kg
GTIN	4013364276499
PU	1 KG
Customs tariff number (Comb. Nomenclature EU)	72202021

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

Strips in different dimensions and materials are available upon request.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component