

DCB YPV 1500 (900 071)

- Einsetzbar in PV-Systemen gemäß IEC 60364-7-712 / DIN VDE 0100-712
- Universell einsetzbar in geerdeten und ungeerdeten PV-Systemen
- Anschlussfertiger Kombi-Ableiter Typ 1 + Typ 2 für Photovoltaik-Generatorstromkreise
- Bewährte fehlerresistente Y-Schaltung vermeidet Schädigung des Überspannungsschutzes bei Isolationsfehlern im Generatorkreis





Basic circuit diagram



Dimension drawing

Kombi-Ableiter für Photovoltaik-Stromversorgungssysteme bis 1500 V DC.

Type	**DCB YPV 1500**
Part No.	**900 071**
Technical data	
SPD according to EN 61643-31 / IEC 61643-31	Typ 1 + Typ 2 / Class I + Class II
Max. PV voltage [DC+ -> DC-] (U_{CPV})	≤ 1500 V
Max. PV voltage [DC+/DC- -> PE] (U_{CPV})	≤ 1500 V
Short-circuit withstand capability (I_{SCPV})	10 kA
Nominal discharge current (8/20 µs) (I_n)	20 kA
Max. discharge current (8/20 µs) (I_{max})	40 kA
Total discharge current (8/20 µs) [DC+/DC- -> PE] (I_{total})	40 kA
Total discharge current (10/350 µs) [DC+/DC- -> PE] (I_{total})	12,5 kA
Lightning impulse current (10/350 µs) [DC+ -> PE/DC- -> PE] (I_{imp})	6,25 kA
Voltage protection level [(DC+/DC-) -> PE] (U_p)	< 4,5 kV
Voltage protection level [DC+ -> DC-] (U_p)	< 4,5 kV
Response time (t_A)	≤ 25 ns
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	grün / rot
Number of ports	1
Cross-sectional area (min.)	1,5 mm² ein- / feindrähtig
Cross-sectional area (max.)	35 mm² mehrdrähtig / 25 mm² feindrähtig
For mounting on	35 mm Hutschiene nach EN 60715
Enclosure material	Thermoplast, Farbe rot, UL 94 V-0
Place of installation	Innenraum
Degree of protection	IP 20
Capacity	4 Standard DIN module, DIN 43880
Approvals	KEMA, UL
Extended technical data	
Use in DC battery storage systems up to I_{SCCR}	≤ 100 kA (t ≤ 5,83 ms)
Backup fuse for DC battery storage systems up to I_{SCCR}	Bussman HLS 2000Vdc / 200 A 2+/A173 DST aR, Herst.Art.Nr.: 170M2040 Mersen Protistor D122SD20C200QF 200A 2000V DC aR

Masterdata	
Net weight	561.58 g/pc(s)
GTIN	6942299504545
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85354000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component