

DVA EMOB M 3P 255 FM (900 585)

- Universally applicable combined lightning current and surge arrester, particularly for use in power supply systems for the charging infrastructure
- Consisting of a base part and pluggable protection module based on RAC spark gap technology
- Only 1 standard DIN module per pole, allows space-saving installation
- Energy-coordinated protection effect with terminal equipment Type 1 + type 2 + type 3
- Residual energy with S20K275 terminal device varistor < 0.5 J
- Maximum backup fuse up to 250 A gG
- Insulation measurement possible up to 500 V DC when connected





Basic circuit diagram



Dimension drawing

Prewired combined lightning current and surge arrester for use in three-phase TT and TN-S systems (3+1 configuration) with remote signalling contact.

NEW

Type	DVA EMOB M 3P 255 FM
Part No.	**900 585**
SPD according to EN 61643-11 / IEC 61643-11	type 1 + type 2 / class I + class II
Energy coordination with terminal equipment (≤ 10 m)	type 1 + type 2 + type 3
Nominal voltage (a.c.) (U_N)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [L-N]/[N-PE] (U_C)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 µs) [L-N]/[N-PE] (I_{imp})	12.5 / 50 kA
Specific energy [L-N]/[N-PE] (W/R)	39.06 kJ/ohms / 625.00 kJ/ohms
Nominal discharge current (8/20 µs) (I_n)	25 / 100 kA
Voltage protection level [L-N]/[N-PE] (U_p)	≤ 1.5 kV / ≤ 1.5 kV
Follow current extinguishing capability [L-N]/[N-PE] (I_{fi})	50 kA_{rms} / 100 A_{rms}
Follow current limitation / Selectivity	No tripping of a 35 A gG fuse up to 50 kA_{rms} (prosp.)
Response time (t_A)	≤ 100 ns
Max. backup fuse (L) up to I_K ≤ 25 kA_{rms}	250 A gG
Max. backup fuse (L) up to I_K ≤ 50 kA_{rms}	250 A gG
Temporary overvoltage (TOV) [L-N] (U_T) – Characteristic	440 V / 120 min. – withstand
Temporary overvoltage (TOV) [N-PE] (U_T) - Characteristic	1200 V / 200 ms – withstand
Operating temperature range [parallel]/[series] (T_U)	-40°C...+80°C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (L1, L2, L3, N, PE,) (min.)	1.5 mm² solid / flexible
Cross-sectional area (L1, L2, L3, N, PE,) (max.)	35 mm² stranded / 25 mm² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 Standard DIN module, DIN 43880
Approvals	KEMA, UL
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm² solid / flexible
Insulation measurement possible when connected	up to 500 V DC

© DEHN (U.K.) LTD. • Unit 4 Velocity Point • Castleton Road • Armley • Leeds • LS12 2EE • United Kingdom • Tel. +44 113 541 8900 • info@dehn.co.uk • www.dehn.co.uk

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

Extended technical data	
Voltage protection level [L-PE] (U_p)	1.8 kV

Masterdata	
Net weight	534.35 g/pc(s)
GTIN	4013364498983
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85354000

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN (U.K.) LTD. • Unit 4 Velocity Point • Castleton Road • Armley • Leeds • LS12 2EE • United Kingdom • Tel. +44 113 541 8900 • info@dehn.co.uk • www.dehn.co.uk

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component