


DCU EMOB 2 32 (900 905)





Basic circuit diagram



Dimension drawing

Junction box for e-mobility.
With surge protection and push-in terminals for the output.

NEW

Type	DCU EMOB 2 32
Part No.	**900 905**
SPD according to EN 61643-11 / IEC 61643-11	Type 2 + Type 3 / class II + class III
Tested to	EN 61439-1 / ... IEC 61439-1 EN 61439-2 / ... IEC 61439-2
Nominal voltage (a.c.) (U_N)	230 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [L-N] (U_C)	275 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) [N-PE] (U_C)	255 V (50 / 60 Hz)
Max. continuous operating voltage DC (U_C)	350 V
Nominal alternating current (I_L)	32 A
Max. power	11 / 22 kW
Nominal discharge current (8/20 µs) [L-N] (I_n)	10 kA
Max. discharge current (8/20 µs) [L-N] (I_{max})	20 kA
Nominal discharge current (8/20 µs) [N-PE] (I_n)	10 kA
Max. discharge current (8/20 µs) [N-PE] (I_{max})	20 kA
Total discharge current (8/20 µs) [L+N-PE] (I_{total})	40 kA
Combination wave [L-N]/[N-PE] (U_{OC})	20 kV
Voltage protection level [L-N] (U_p)	≤ 1.5 kV
Voltage protection level [N-PE] (U_p)	≤ 1.5 kV
Follow current extinguishing capability [N-PE] (I_{Fi})	100 A_{eff}
Response time [L-N] (t_A)	25 ns
Response time [L/N-PE] (t_A)	100 ns
Max. mains-side overcurrent protection (parallel connection)	40 A gG
Short-circuit withstand capability for mains-side overcurrent protection (I_{SCCR})	6 kA_{rms}
Temporary overvoltage (TOV) [L-N] (U_T) – Characteristic	335 V / 5 sec. – withstand 440 V / 120 min. – safe failure
Temporary overvoltage (TOV) [N-PE] (U_T) - Characteristic	1200 V / 200 ms – withstand
Insulation measurement	up to 500 V DC when connected
Operating state / fault indication	green / red
Cross-sectional area for push-in terminals	0.5 ... 16 mm² solid / fine-stranded
Type of remote signalling contact	Changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm² solid / fine-stranded
Place of installation	Installation in protected outdoor areas
Degree of protection	IP 65
Type	with pressure compensating element
Cover	Transparent cover with product label
Enclosure colour	grey
Input	Ölflex 5x 6 mm², length 1.5 m
Output	System-side connection with M25 screw connection
Enclosure dimensions (b x h x d)	182 x 180 x 100 mm

Masterdata	
Net weight	1.53 kg/pc(s)
GTIN	4013364506244
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85371098

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component