

DEHNrapid LSA – Lightning Current / Surge Arrester


DRL 10 B 180 (907400)

- Lightning current arrester for use as plug-in SPD block with integrated LSA disconnection block function
- Expandable to a combined lightning current and surge arrester
- For installation in conformity with the lightning protection zone concept at the boundaries from 0_A – 1 and higher





Basic circuit diagram



Dimension drawing

Lightning current carrying DRL plug-in SPD block (10 pairs) with three-pole gas discharge tubes for almost all applications. Expandable to a combined lightning current and surge arrester by means of a DRL protective plug. The integrated disconnection block contacts allow testing, measuring and patching with plugged-in protection.

Type	**DRL 10 B 180**
Part No.	**907400**
SPD class	TYPE 1C
Nominal voltage (U_N)	180 V
Max. continuous operating voltage DC (U_C)	180 V
Max. continuous operating a.c. voltage (U_C)	127 V
Nominal current (I_N)	0.4 A
D1 Total lightning impulse current (10/350 µs) (I_{imp})	5 kA
D1 Lightning impulse current (10/350 µs) per line (I_{imp})	2.5 kA
C2 Total nominal discharge current (8/20 µs) (I_n)	10 kA
C2 Nominal discharge current (8/20 µs) per line (I_n)	5 kA
Voltage protection level line-line for I_{imp} D1 (U_P)	≤ 850 V
Voltage protection level line-PG for I_{imp} D1 (U_P)	≤ 600 V
Voltage protection level line-line at 1 kV/µs C3 (U_P)	≤ 850 V
Voltage protection level line-PG at 1 kV/µs C3 (Up)	≤ 600 V
Series impedance per line	≤ 0.005 ohms
Capacitance line-line (C)	≤ 5 pF
Capacitance line-PG (C)	≤ 5 pF
Operating temperature range (T_U)	-40 °C ... +80 °C
Degree of protection	IP 10
Pluggable into	LSA disconnection block 2/10
Earthing via	mounting frame
Enclosure material	polyamide PA 6.6
Colour	grey
Test standards	IEC 61643-21 / EN 61643-21

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364107557
PU	1 st

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.