
DEHNrapid LSA – Lightning Current / Surge Arrester


DRL PD 180 (907430)

- For maximum transmission rates - combined with overcurrent protection
- Energy-coordinated with DRL plug-in SPD block
- For installation in conformity with the lightning protection zone concept at the boundaries from 1 – 2 and higher





Basic circuit diagram



Dimension drawing

Protective plug (one pair), energy-coordinated with DRL plug-in SPD block, for use as single-stage protective device for terminal equipment. Low voltage protection level line-line and integrated overcurrent protection for ADSL, ISDN U_{k0} or a/b lines. To be mounted into EF 10 DRL. Installation recommended only in combination with DRL plug-in SPD block.

Type	**DRL PD 180**
Part No.	**907430**
SPD class	TYPE 3 P1
Nominal voltage (U_N)	180 V
Max. continuous operating voltage DC (U_C)	180 V
Max. continuous operating a.c. voltage (U_C)	127 V
Nominal current (I_N)	0.1 A
D1 Total lightning impulse current (10/350 µs) in combination with DRL 10 B... (I_{imp})	5 kA
D1 Lightning impulse current (10/350 µs) per line in combination with DRL 10 B... (I_{imp})	2.5 kA
C2 Total nominal discharge current (8/20 µs) in combination with DRL 10 B... (I_n)	10 kA
C2 Nominal discharge current (8/20 µs) per line in combination with DRL 10 B... (I_n)	5 kA
C1 Nominal discharge current (8/20 µs) per line without DRL 10 B... (I_n)	0.25 kA
Voltage protection level line-PG for I_{imp} D1 in combination with DRL 10 B... (U_p)	≤ 500 V
Voltage protection level line-line at 1 kV/µs C3 (U_p)	≤ 270 V
Series impedance per line	10 ohms +/- 15%
Cut-off frequency line-line (f_G)	61 MHz
Capacitance line-line (C)	≤ 80 pF
Type	integrated overcurrent protection
Operating temperature range (T_U)	0 °C ... +70 °C
Degree of protection	IP 20 (when plugged in)
Pluggable into	LSA disconnection block 2/10 or DRL 10 B... plug-in SPD block
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21

Masterdata	
Net weight	1 pc(s)/st
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364107670
PU	10 st

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.