


DG MU 3PY 480 4W+G R (908 346)

- Prewired complete unit without the need for additional surge protective devices
- High discharge capacity due to heavy-duty zinc oxide varistors ($I_{max.}$ 50 kA 8/20)
- Short-circuit current rating (SCCR) 200 kA
- ANSI/UL 1449 open-type 1 SPD





Basic circuit diagram



Dimension drawing

DIN rail mount, pluggable surge arrester consisting of a base part and plug-in protection modules for application in 3 Phase Wye Systems; has floating Form C (SPDT) remote status contacts

Type	**DG MU 3PY 480 4W+G R**
Part No.	**908 346**
Standards	
Certification	UL
UL Standard	UL 1449 5th edition
UL File Number	E319777
Test values according to UL 1449	
Type (SPD classification)	Type 1 component assembly
Voltage protection rating (VPR)	1,200 / 1,800 / 2,500 / 600 V
Nominal discharge current (8/20µs) (I_n)	20 kA
Maximum ambient temperature	85 °C
AWG (conductors)	4-14 Cu solid or stranded
Torque (conductors)	35 - 45 Lbs-in
AWG (remote indicator)	16 - 22 Cu
Torque (remote indicator)	3 Lbs-in
Technical data	
SPD as per ANSI/UL 1449	□□□□□□□ 1 SPD
UL 1449 edition	5th edition
SPD as per CSA-C22.2 no. 269.1	Type 4-1 Component Assembly
Nominal system voltage [L-N] / [L-G] / [L-L] / [N-G] (U_N)	277 V a.c. / 277 V a.c. / 480 V a.c. / 0 V a.c.
Frequency	50 / 60 Hz
Max. continuous operating voltage AC [L-N] / [L-G] / [L-L] / [N-G] (MCOV)	385 V a.c. / 565 V a.c. / 770 V a.c. / 180 V a.c.
Nominal discharge current (8/20 µs) (I_n)	20 kA
Voltage protection rating [L-N] / [L-G] / [L-L] / [N-G] (VPR)	1200 V_{pk} / 1800 V_{pk} / 2500 V_{pk} / 600 V_{pk}
Max. mains-side overcurrent protection	Not needed
Short circuit current rating (SCCR)	200 kA
System type	3 Phase Wye
Operating temperature range (T_U)	-40°C...+85°C
Operating state / fault indication	Green = Good ; Red = Replace Module
Cross-sectional area (min.)	14 AWG / 2.5 mm²
Cross-sectional area (max.)	4 AWG / 25 mm²
Terminal Torque Ratings	35-45 Lbs-in
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Degree of protection	IP 20
Capacity	4 Standard DIN module, DIN 43880
Approvals	UL, CSA
Type of remote signalling contact	Floating (dry), Form C (SPDT)
Remote status NEC circuits	NEC Class 2 circuits only
Cross-sectional area for remote signalling terminals	AWG 16-22 / 1.5 mm² - 0.34mm²
Remote Status Terminal Torque Ratings	3 Lbs-in

Extended technical data	
Max. discharge current (8/20) (I_{max})	50 kA

Masterdata	
Net weight	432.3 g/pc(s)
GTIN	4013364148871
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363030

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component