

SFL PRO 6X 19“ (909 251)

- Surge protection with monitoring device and disconnector
- Interference suppressor filter
- Visual operating state (green) and fault indication (red)





Basic circuit diagram



Dimension drawing

Surge protective multiple socket outlet with mains filter for 482.6 mm (19 inches) data cabinets.

Type	**SFL PRO 6X 19“**
Part No.	**909 251**
SPD according to EN 61643-11 / IEC 61643-11	type 3 / class III
Nominal voltage (a.c.) (U_N)	230 V (50 / 60 Hz)
Max. continuous operating voltage (AC) (U_C)	255 V (50 / 60 Hz)
Nominal load current (a.c.) (I_L)	16 A
Voltage drop in percent for U_C/I_L (ΔU)	≤ 0.5 %
Nominal discharge current (8/20 µs) (I_n)	3 kA
Total discharge current (8/20 µs) [L+N-PE] (I_{total})	5 kA
Combination wave (U_{OC})	6 kV
Combination wave [L+N-PE] ($U_{OC\ total}$)	10 kV
Voltage protection level (U_p)	≤ 1.6 kV
Response time [L-N] (t_A)	≤ 25 ns
Response time [L/N-PE] (t_A)	≤ 100 ns
Max. mains-side overcurrent protection	B 16 A
Short-circuit withstand capability for max. mains-side overcurrent protection (I_{SCCR})	1.5 kA_{rms}
Temporary overvoltage (TOV) [L-N] (U_T) – Characteristic	335 V / 5 sec. – Festigkeit 440 V / 120 min. – sicherer Ausfall
Temporary overvoltage (TOV) [L/N-PE] (U_T) – Characteristic	335 V / 120 min. – Festigkeit 440 V / 5 sec. – Festigkeit
Temporary overvoltage (TOV) [L+N-PE] (U_T) – Characteristic	1200 V + U_{REF} / 200 ms – safe failure
Fault indication	red light
Operating state indication	green light
Number of ports	2
Operating temperature range (T_U)	-20 °C ... +40 °C
Connecting cable	approx. 2000 mm
Number of socket outlets	6
Mounting	earthed socket outlets DIN 49440 / DIN 49441
Enclosure material	anodised aluminium profile, silver
Place of installation	indoor installation
Degree of protection	IP 20
Dimensions	483 x 44 x 44 mm
Mains filter	acc. to EN 60393-1 (DIN VDE 0565-3)
Attenuation for f = 1 MHz, balanced	≥ 32 dB
Attenuation for f = 1 MHz, unbalanced	≥ 30 dB

Masterdata	
Net weight	877 g/pc(s)
GTIN	4013364132573
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363010

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component