DRC LC M1+ (910 655)

- For the quick inspection of arresters with RFIDLifeCheck
- Hand-held equipment, easy to transport and operate
- Country-specific adapter for charging unit



Portable device with LifeCheck sensor for flexible use. For the quick inspection of arresters with RFID LifeCheck. Operation and charge indication and the result indication of the LifeCheck test are provided through LEDs. The DRC LC M1+ is equipped with an RFID snap-on LifeCheck sensor.

Type	**DRC LC M1+**
Part No.	**910 655**
For testing	BLITZDUCTOR XT / XTU ML
Testing of BXT ML EX	**BLITZDUCTOR XT ML EX: for use in non-hazardous atmospheres only!**
Voltage supply (included in delivery)	lithium-polymer battery
RFID transmission frequency	125 kHz
Measured value indication	LED
Testing period	typically 3 to 10 sec.
Operating temperature range	-20 °C ... +60 °C
Battery test	automatically switched off in case of empty batteries
Cable length to the LifeCheck sensor	approx. 1000 mm
Dimensions of the LifeCheck sensor	90 x 51 x 12 mm
Dimensions of the hand-held device	122 x 69 x 33 mm
Delivery includes	hand-held device, BXT LifeCheck sensor, power supply unit with country-specific adapters, USB cable, test module for reference, storage case
Dimensions of the storage case	275 x 230 x 83 mm

Masterdata	
Net weight	834.6 g/pc(s)
GTIN	4013364149250
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	90308900

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.