SA KRF 29 V2A (919 034)

- For solderless connection of a conductor to the shield
- For use with all plastic and lead-sheathed cables
- Also suitable for steel-reinforced lead-sheathed cables



Constant force springs allow solderless shield connections for equipotential bonding or lightning equipotential bonding. They can be installed subsequently without interrupting the cable shield or requiring tools for installation.

Type	**SA KRF 29 V2A**
Part No.	**919 034**
Lightning impulse current carrying capability (10/350 µs)	10 kA
Clamping range Rd	18.5-29 mm
Material	StSt
Colour	bare surface
For mounting on	cable shields
Width	16 mm

Masterdata	
Net weight	7.2 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	73209090
GTIN	4013364103542
PU	10 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • : Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component