
SDS 4 (923 118)

- Electrical isolation of insulated track sections and earthed parts of installations
- Safe equipotential bonding due to high-current-resistant welding of the electrodes in case of a short-circuit or earth fault at the overhead contact line
- Discharge of surges without short-circuit formation





Dimension drawing

Voltage limiting device for a d.c. sparkover voltage of 230 V.

Type	**SDS 4**
Part No.	**923 118**
VLD type (EN 50122-1)	VLD-F
d.c. sparkover voltage (U_{ag})	230 V +/- 20%
Impulse sparkover voltage	≤ 650 V (1 kV/µs)
Lightning current discharge capacity (10/350 µs) 0.1x / 0.5x / 1x	2.5 kA
Lightning current carrying capability (10/350 µs)	25 kA
Impulse current discharge capacity (8/20 µs) 0.1x / 0.5x / 1x	20 kA
Safe short-circuit due to welding of the electrodes in case of direct currents	≥ 600 A / 250 ms
Additional short-circuit current rating	25 kA_{rms} / 100 ms; 36 kA_{rms} / 75 ms
Long-term current	1 kA_{rms} for t ≤ 120 s
Leakage current (I_{lc})	< 1 µA for 100 V d.c.
Operating temperature range (T_U)	-40 °C ... +80 °C
To be mounted with	mast adapter MA SDS M12 or SIEMENS No. 8WL6503-xx

Masterdata	
Net weight	38.3 g/pc(s)
GTIN	4013364104969
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85369095

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.