

BCO CL2 BD HC10A 24 (927 408)

- Two-pole arrester for protecting DC supplies of up to 10 A nominal current
- LifeCheck arrester monitoring and integrated status indication
- For installation in conformity with the lightning protection zone concept at the boundaries from 0_A – 2 and higher





Basic circuit diagram



Dimension drawing

Space-saving, compact combined arrester with a width of 12 mm and push-in connection technology with status indication for protecting one pair in unearthed DC supplies for IT systems and measuring and control circuits.

Type	**BCO CL2 BD HC10A 24**
Part No.	**927 408**
Standards	
Certification	UL
UL Standard	UL 497b
UL File Number	E156818
Test values according to UL 497b	
Type (SPD classification)	BCO CL2 BD HC10A
Strike voltage Line to Ground 100 V/s min.	53.4 V
Strike voltage Line to Ground 100 V/s max.	59 V
Strike voltage Line to Line 100 V/s max.	108 V
Technical data	
SPD class	TYPE 1 P2
Impulse category	D1, C1, C2, C3, B2
Nominal voltage (U_N)	24 V
Max. continuous operating voltage DC (U_C)	45 V
Max. continuous operating a.c. voltage (U_C)	31.8 V
Nominal current at 80°C (I_L)	10 A
D1 Total lightning impulse current (10/350 µs) (I_{imp})	5 kA
D1 Lightning impulse current (10/350 µs) per line (I_{imp})	2.5 kA
C2 Total nominal discharge current (8/20 µs) (I_n)	20 kA
C2 Nominal discharge current (8/20 µs) per line (I_n)	10 kA
Voltage protection level line-line for I_n 1 kA C2 (U_p)	≤ 100 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 800 V
Voltage protection level line-PG at 1 kV/µs C3 (U_p)	≤ 800 V
Series resistance per line	0 Ohm
Cut-off frequency line-line at 100 ohms (f_G)	2 MHz
Capacitance line-line (C)	≤ 1.37 nF
Capacitance line-PG (C)	≤ 13.06 pF
Operating temperature range (T_U)	-40°C to +80°C
Operating state / fault indication	green / red
Degree of protection	IP 20
Connection (input / output)	Push-in / Push-in
Cross-sectional area, solid	0.2-2.5 mm²
Cross-sectional area, flexible	0.2-2.5 mm²
Earthing via	35 mm DIN rails acc. to EN 60715
Enclosure material	Polyamide PA 6.6, UL 94 V-0
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21
Approvals	UL 497B, SIL

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

Technical data	
SIL classification	up to SIL3 *)

Masterdata	
Net weight	52.1 g/pc(s)
GTIN	4013364463653
PU	1 pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363010

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) For details, see: www.dehn-international.com