
DEHNpatch – Arrester for Data Networks and Ethernet Applications


DPA M CLD RJ45B 48 (929126)

- Ideally suited for retrofitting, protection of all lines
- For use in structured cabling systems according to class D up to 100 MHz
- Power over Ethernet IEEE 802.3 compliant (up to PoE++ / 4PPoE)
- For installation in conformity with the lightning protection zone concept at the boundaries from 0_B – 2 and higher





Basic circuit diagram



Dimension drawing

Universal arrester for Industrial Ethernet, Power over Ethernet (IEEE 802.3 compliant up to PoE++ / 4PPoE) and similar applications in structured cabling systems according to class D up to 100 MHz. Protection of all pairs by powerful gas discharge tubes. DIN rail mounted adapter type with sockets.

Type	**DPA M CLD RJ45B 48**
Part No.	**929126**
Standards	
Certification	UL
UL Standard	UL 497b
UL File Number	E156818
Test values according to UL 497b	
Type (SPD classification)	DPA M CLD RJ45B 48
Strike voltage Line to Line 100 V/s min.	70 V
Strike voltage Line to Line 100 V/s max.	115 V
Strike voltage Line to Ground 100 V/s min.	70 V
Strike voltage Line to Ground 100 V/s max.	115 V
Technical data	
SPD class	TYPE 2 P2
Nominal voltage (U_N)	48 V
Max. continuous operating voltage (d.c.) (U_c)	48 V
Max. continuous operating voltage (a.c.) (U_c)	34 V
Max. continuous operating voltage (d.c.) pair-pair (PoE) (U_c)	57 V
Nominal current (I_N)	1 A
D1 Lightning impulse current (10/350 µs) per line (I_{imp})	0.5 kA
C2 Nominal discharge current (8/20 µs) line-line (I_n)	1.25 kA
C2 Nominal discharge current (8/20 µs) line-PG (I_n)	2.5 kA
C2 Nominal discharge current (8/20 µs) pair-pair (PoE) (I_n)	2.5 kA
C2 Total nominal discharge current (8/20 µs) (I_n)	10 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 700 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 700 V
Voltage protection level line-line for I_n C2 (PoE) (U_p)	≤ 900 V
Voltage protection level line-line at 1 kV/µs C3 (U_p)	≤ 600 V
Voltage protection level line-PG at 1 kV/µs C3 (Up)	≤ 500 V
Voltage protection level pair-pair at 1 kV/µs C3 (PoE) (U_p)	≤ 700 V
Cut-off frequency (f_G)	100 MHz
Insertion loss at 100 MHz	≤ 3 dB
Capacitance line-line (C)	≤ 10 pF
Capacitance line-PG (C)	≤ 10 pF

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component

Technical data	
Operating temperature range (T_U)	-40 °C ... +80 °C
Degree of protection	IP 10
For mounting on	35 mm DINs rails acc. to EN 60715
Connection (input / output)	RJ45 socket / RJ45 socket
Pinning	1/2, 3/6, 4/5, 7/8
Earthing via	35 mm DINs rails acc. to EN 60715
Enclosure material	zinc die-cast
Colour	bare surface
Test standards	IEC 61643-21 / EN 61643-21
Approvals	UL 497B

Masterdata	
Net weight	96 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364242258
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

© DEHN, Inc. • 500 S Main Street, Suite 115 • Mooresville, NC 28115 • United States • Tel. +1 877-927-6510 • contactDEHN@dehn.us • www.dehn.us

: Tested • NEU: New • !: Discontinued Model
: Cross connector • : Longitudinal connector • : Parallel connector • : T connector • : Clamp for parallel connector • : Clamp for T connector
: Pipe clamp for parallel connector • : Pipe clamp for T connector • : Equipotential bonding bar • : Bridging component