
DEHNpipe


DPI CD EXD 24 N (929964)

- Easy to mount on the spare cable gland of field devices
- Ex(d) type for universal use
- For installation in conformity with the lightning protection zone concept at the boundaries from 0_B – 2 and higher





Basic circuit diagram



Dimension drawing

Flameproof surge arrester with a low-capacitance protective circuit for protecting measuring circuits and bus systems in potentially explosive atmospheres. Insulation strength > 500 V to earth. Certified to CSA and USA Hazloc standards.

Type	**DPI CD EXD 24 N**
Part No.	**929964**
Standards	
Certification	UL
UL Standard	UL 497b
UL File Number	E156818
Technical data	
SPD class	TYPE 2 P1
Nominal voltage (U_N)	24 V
Max. continuous operating voltage DC (U_C)	32 V
Max. continuous operating a.c. voltage (U_C)	22,6 V
Nominal current (I_N)	0,55 A
D1 Lightning impulse current (10/350 µs) line-PG (I_{imp})	1 kA
C2 Total nominal discharge current (8/20 µs) (I_n)	10 kA
C2 Nominal discharge current (8/20 µs) per line (I_n)	10 kA
Voltage protection level line-line for I_n C2 (U_P)	≤ 58 V
Voltage protection level line-PG for I_n C2 (U_P)	≤ 1700 V
Voltage protection level line-line at 1 kV/µs C3 (U_P)	≤ 50 V
Voltage protection level line-PG at 1 kV/µs C3 (Up)	≤ 1200 V
Cut-off frequency line-line (f_G)	67 MHz
Capacitance line-line (C)	≤ 25 pF
Capacitance line-PG (C)	≤ 15 pF
Operating temperature range (T_U)	-50 °C ... +80 °C
Degree of protection	Aufbau in IP 67
For mounting on (field / device side)	$^1/_2$-14 NPT Außengewinde
Connection	Anschlussleitungen 1,3 mm²
Length of the connecting lead	250 mm
Earthing via	Anschlussleitung
Enclosure material	NIRO (V4A)
Colour	blank
Test standards	IEC 61643-21 / EN 61643-21
Approvals	ATEX, IECEx, CCC, CSA & USA Hazloc, SIL
ATEX approvals	KEMA 04ATEX2190 X: II 2 G Ex db IIC T5 or T6 Gb
IECEx approvals	KEM 09.0064X: Ex db IIC T5 or T6 Gb
CSA & USA Hazloc approvals (1)	CSA 10.2317168: Ex d IIC T4 ... T6
CSA & USA Hazloc approvals (2)	CSA 10.2317168: Class I Div 1, 2; Class I Zone 1
China Compulsory Certification	CCC No. 2021312304001029
SIL classification	up to SIL3 *)

Protection for the data side	
For mounting on (field / device side)	x

Masterdata	
Net weight	169 g/pc(s)
Customs tariff number (Comb. Nomenclature EU)	85363010
GTIN	4013364101814
PU	1 pc(s)

We reserve the right to make changes to the design and technology, dimensions, weights and materials in the interests of technical progress. The illustrations are not binding.

*) For details, see: www.dehn-international.com